

# **RYOBI**

**KATALOG RIBOLOVNO PRIBORA 2021**

**[WWW.BBS-SPORT.HR](http://WWW.BBS-SPORT.HR)**

- NCRT NEW COMPOSITE MATERIAL, 20% LIGHTER AND 40% STRONGER THAN NORMAL PLASTIC MATERIAL
- V-SHAPED NCRT ROTOR ARM.
- V-SHAPED LARGE SPOOL.
- METAL BODY CONSTRUCTION.
- SLOW OSCILLATION SYSTEM.



# ZAUBER PRO HP

METAL BODY SPINNING REEL

- 8 ball bearings, 1 roller bearing.
- Multi section front drag.
- Metal body construction.
- Slow oscillation system
- NCRT new composite material makes reel 20% lighter and 40% stronger than normal plastic material.
- Drag knob have waterproof ring, which effectively stops water and impurity.
- Thread bail arm made by stainless steel keeps no gap and intensity.
- Hi-intensity titanium main shaft.



| SIZE | BB  | GEAR RATIO | WEIGHT | MM/M                          | MAX DRAG |
|------|-----|------------|--------|-------------------------------|----------|
| 1000 | 8+1 | 5.1:1      | 231g   | 0.205-150 0.235-115 0.285-80  | 2.5kg    |
| 2000 | 8+1 | 5.1:1      | 233g   | 0.235-155 0.285-110 0.330-80  | 2.5kg    |
| 3000 | 8+1 | 5.0:1      | 271g   | 0.235-235 0.285-170 0.330-115 | 5.0kg    |
| 4000 | 8+1 | 5.0:1      | 273g   | 0.285-200 0.330-150 0.370-115 | 5.0kg    |

# LEGACY SW

- 5 ball bearings, 1 roller bearing.
- Multi section front drag.
- New rotaty flat oscillation system.
- All screws and main shaft of high grade stainless and effective avoiding corrosive by sea.
- New design of spool's margin makes line sliding smoothly, and target farer and more accurate.
- Thread ball arm made of by stainless steel keeps no gap and intensity.



| SIZE | BB  | GEAR RATIO | WEIGHT | MM/M                          | MAX DRAG |
|------|-----|------------|--------|-------------------------------|----------|
| 1000 | 5+1 | 5.1:1      | 255g   | 0.205-150 0.235-115 0.285-80  | 2.5kg    |
| 2000 | 5+1 | 5.1:1      | 257g   | 0.235-155 0.285-110 0.330-80  | 2.5kg    |
| 3000 | 5+1 | 5.0:1      | 305g   | 0.235-235 0.285-170 0.330-115 | 5.0kg    |
| 4000 | 5+1 | 5.0:1      | 308g   | 0.285-200 0.330-150 0.370-115 | 5.0kg    |

## VERTIGO II

- 6 ball bearings, 1 roller bearing.
- Multi section front drag.
- New rotary flat oscillation system.
- All screws and main shaft of high grade stainless and effective avoiding corrosive by sea.
- New design of spool's margin makes line sliding smoothly, and target farer and more accurate.
- Thread ball arm made of by stainless steel keeps no gap and intensity.



| SIZE | BB  | GEAR RATIO | WEIGHT | MM/M                | MAX DRAG |
|------|-----|------------|--------|---------------------|----------|
| 1000 | 6+1 | 5.1:1      | 239g   | 0.205-155 0.235-120 | 2.5kg    |
| 2000 | 6+1 | 5.1:1      | 241g   | 0.235-160 0.285-110 | 2.5kg    |
| 3000 | 6+1 | 5.0:1      | 270g   | 0.235-250 0.285-180 | 5.0kg    |
| 4000 | 6+1 | 5.0:1      | 273g   | 0.285-220 0.330-165 | 5.0kg    |

## NEXUS C<sup>PRO</sup>

NEW ROTARY FLAT OSCILLATION SYSTEM

- 6 ball bearings, 1 roller bearing.
- Multi section front drag.
- Mteal body construction.
- Slow oscillation system
- NCRT new composite material makes reel 20% lighter and 40% stronger than normal plastic material.
- Drag knob have waterproof ring, which effectively stops water and impurity.
- Thread bail arm made by stainless steel keeps no gap and intensity.
- Hi-intensity titanium main shaft.



| SIZE | BB  | GEAR RATIO | WEIGHT | MM/M                          | MAX DRAG |
|------|-----|------------|--------|-------------------------------|----------|
| 1000 | 6+1 | 5.1:1      | 242g   | 0.205-145 0.235-115 0.285-80  | 3.0kg    |
| 2000 | 6+1 | 5.1:1      | 245g   | 0.235-155 0.285-110 0.330-80  | 3.0kg    |
| 3000 | 6+1 | 5.0:1      | 282g   | 0.235-235 0.285-170 0.330-115 | 5.0kg    |
| 4000 | 6+1 | 5.0:1      | 285g   | 0.285-200 0.330-150 0.370-115 | 5.0kg    |

# ZEUS HP

POWER SCREW IN HANDLE

- 6 ball bearings, 1 roller bearing.
- Multi section front drag.
- New rotaty flat oscillation system.
- All screws and main shaft of high grade stainless and effective avoiding corrosive by sea.
- New design of spool's margin makes line sliding smoothly, and target farer and more accurate.
- Thread ball arm made of by stainless steel keeps no gap and intensity.



| SIZE | BB  | GEAR RATIO | WEIGHT | MM/M                | MAX DRAG |
|------|-----|------------|--------|---------------------|----------|
| 1000 | 6+1 | 5.1:1      | 254g   | 0.205-155 0.235-120 | 2.5kg    |
| 2000 | 6+1 | 5.1:1      | 257g   | 0.235-160 0.285-110 | 2.5kg    |
| 3000 | 6+1 | 5.0:1      | 285g   | 0.235-250 0.285-180 | 5.0kg    |
| 4000 | 6+1 | 5.0:1      | 288g   | 0.285-220 0.330-165 | 5.0kg    |
| 5000 | 6+1 | 5.0:1      | 395g   | 0.330-200 0.370-160 | 7.5kg    |
| 6000 | 6+1 | 5.0:1      | 398g   | 0.330-230 0.370-200 | 7.5kg    |
| 8000 | 6+1 | 5.0:1      | 558g   | 0.405-200 0.435-160 | 10.0kg   |

# ACCURIST

NEW ROTARY FLAT OSCILLATION SYSTEM

- 4 ball bearings, 1 roller bearing.
- Multi section front drag.
- New rotaty flat oscillation system.
- All screws and main shaft of high grade stainless and effective avoiding corrosive by sea.
- New design of spool's margin makes line sliding smoothly, and target farer and more accurate.
- Thread ball arm made of by stainless steel keeps no gap and intensity.



| SIZE | BB  | GEAR RATIO | WEIGHT | MM/M                          | MAX DRAG |
|------|-----|------------|--------|-------------------------------|----------|
| 1000 | 4+1 | 5.1:1      | 239g   | 0.205-150 0.235-115 0.285-80  | 3.0kg    |
| 2000 | 4+1 | 5.1:1      | 241g   | 0.235-155 0.285-110 0.330-80  | 3.0kg    |
| 3000 | 4+1 | 5.0:1      | 270g   | 0.235-235 0.285-170 0.330-115 | 5.0kg    |
| 4000 | 4+1 | 5.0:1      | 273g   | 0.285-200 0.330-150 0.370-115 | 5.0kg    |

**VARIUS**  
SUPER HI-SPEED

- Fully aluminum body that can achieved the over all strength, While reducing the weight.
- Higher cranking power and better endurance with the new (0.6)large modular high-strength gear.
- Larger anti-reverse mechanism with dual-clutch system comes
- With the anti-reverse pawl for better reliability and protection.
- Comes with extra-long stem crank handle self-interchangeable.
- Strong CNC machined line guide bracket.
- Ergonomic handle knob.
- Easy side cover installation and quick remover.
- Dual bearing pinion gear supported to improve strength and durability.
- Karger line capacity.
- Add on protective bar to prevent line damage from reel body.
- Super smooth carbon drag washers.
- Synchronized level-wind line guide system.
- Comes with wrench and line picker for maintenance use.



|                |                     |
|----------------|---------------------|
| Gear Ratio     | 6.8:1               |
| Weight         | 345g                |
| Max.drag Power | 12g                 |
| Ball Bearing   | 10+1                |
| Ling Capacity: | PE1.5-350M PE2-300M |
|                | PE2.5-250M PE3-200M |





**Kontakt: 01 2303 435**

**E-Mail: [info@bbs-sport.hr](mailto:info@bbs-sport.hr)**

**[WWW.BBS-SPORT.HR](http://WWW.BBS-SPORT.HR)**